



Logius
*Ministerie van Binnenlandse Zaken en
Koninkrijksrelaties*

Programme of Requirements part 3c: Certificate Policy - Citizen Domain

Date 8 February 2019

Authenticity	2.16.528.1.1003.1.2.3.1
Non repudiation	2.16.528.1.1003.1.2.3.2
Confidentiality	2.16.528.1.1003.1.2.3.3

Publisher's imprint

Version number 4.7
Contact person Policy Authority of PKIoverheid

Organization Logius

Street address

Wilhelmina van Pruisenweg 52

Postal address

P.O. Box 96810
2509 JE THE HAGUE

T 0900 - 555 4555
servicecentrum@logius.nl

Contents

Contents	3
1 Introduction to the Certificate Policy	7
1.1 Overview.....	7
1.1.1 Design of the Certificate Policy.....	7
1.1.2 Status.....	8
1.2 References to this CP.....	8
1.3 User Community.....	9
1.4 Certificate Usage.....	9
1.5 Contact information Policy Authority.....	10
2 Publication and Repository Responsibilities	11
2.1 Electronic Repository.....	11
2.2 Publication of TSP information.....	11
3 Identification and Authentication	12
3.1 Naming.....	12
3.2 Initial Identity Validation.....	12
3.3 Identification and Authentication for Re-key Requests.....	12
4 Certificate Life-Cycle Operational Requirements	13
4.1 Certificate Application.....	13
4.4 Certificate Acceptance.....	13
4.5 Key Pair and Certificate Usage.....	13
4.9 Certificate Revocation and Suspension.....	13
4.10 Certificate Status Service.....	14
5 Facility, Management and Operational Controls	15
5.2 Procedural Controls.....	15
5.3 Personnel Controls.....	15
5.4 Audit Logging Procedures.....	15
5.5 Records Archival.....	15
5.7 Compromise and Disaster Recovery.....	15
6 Technical Security Controls	16
6.1 Key Pair Generation and Installation.....	16
6.2 Private Key Protection and Cryptographic Module Engineering Controls.....	16
6.3 Other Aspects of Key Pair Management.....	17
6.4 Activation data.....	17

6.5	<i>Computer Security Controls</i>	17
6.6	<i>Life Cycle Technical Controls</i>	17
6.7	<i>Network Security Controls</i>	18
7	Certificate, CRL and OSCP profiles	19
7.1	<i>Certificate Profile</i>	19
7.2	<i>CRL Profile</i>	19
7.3	<i>OCSP Profile</i>	19
8	Compliance Audit and Other Assessments	20
9	Other Business and Legal Matters	21
9.2	<i>Financial Responsibility</i>	21
9.5	<i>Intellectual Property Rights</i>	21
9.6	<i>Representations and Warranties</i>	21
9.8	<i>Limitations of Liability</i>	21
9.12	<i>Amendments</i>	21
9.13	<i>Dispute Resolution Procedures</i>	22
9.14	<i>Governing Law</i>	22
9.17	<i>Other provisions</i>	22
Appendix A	Certificate profiles	23
10	Revisions	32
10.1	<i>Amendments from version 4.6 to 4.7</i>	32
10.1.1	<i>New</i>	32
10.1.2	<i>Modifications</i>	32
10.2	<i>Amendments from version 4.5 to 4.6</i>	32
10.2.1	<i>Modifications</i>	32
10.3	<i>Amendments from version 4.4 to 4.5</i>	32
10.3.1	<i>New</i>	32
10.3.2	<i>Modifications</i>	32
10.3.3	<i>Editorial</i>	32
10.4	<i>Amendments from version 4.3 to 4.4</i>	32
10.4.1	<i>New</i>	32
10.4.2	<i>Modifications</i>	33
10.4.3	<i>Editorial</i>	33
10.5	<i>Amendments from version 4.2 to 4.3</i>	33
10.5.1	<i>New</i>	33
10.5.2	<i>Modifications</i>	33
10.5.3	<i>Editorial</i>	33
10.6	<i>Amendments from version 4.1 to 4.2</i>	33
10.6.1	<i>New</i>	33
10.6.2	<i>Modifications</i>	33
10.6.3	<i>Editorial</i>	33
10.7	<i>Amendments from version 4.0 to 4.1</i>	33

10.7.1	New	33
10.7.2	Modifications	33
10.7.3	Editorial	34
<i>10.8</i>	<i>Amendments from version 3.7 to 4.0</i>	<i>34</i>
10.8.1	New	34
10.8.2	Modifications	34
10.8.3	Editorial	34

The Policy Authority (PA) of the PKI for the government supports the Minister of the Interior and Kingdom Relations in managing the PKI for the government.

The PKI for the government is an agreements system. This system enables generic and large-scale use of the electronic signature, and it also facilitates remote identification and confidential communication.

The tasks of the PA of PKIoverheid are:

- contributing towards the development and the maintenance of the framework of standards that underlies the PKI for the government, the Programme of Requirements (PoR);
- assisting in the process of admittance by TrustService Providers (TSPs) to the PKI for the government and preparing the administration;
- supervising and monitoring the activities of TSPs that issue certificates under the root of the PKI for the government.

The purpose of the Policy Authority is:

Enforcement of a practicable and reliable framework of standards for PKI services that provides an established level of security for the government's communication needs that is transparent to users.

Revision control

Version	Date	Description
4.0	12-2014	Ratified by the Ministry of the Interior and Kingdom Relations December 2014
4.1	07-2015	Ratified by the Ministry of the Interior and Kingdom Relations July 2015
4.2	01-2016	Ratified by the Ministry of the Interior and Kingdom Relations January 2016
4.3	07-2016	Ratified by the Ministry of the Interior and Kingdom Relations July 2016
4.4	02-2017	Ratified by the Ministry of the Interior and Kingdom Relations February 2017
4.5	07-2017	Ratified by the Ministry of the Interior and Kingdom Relations July 2017
4.6	01-2018	Ratified by the Ministry of the Interior and Kingdom Relations January 2018
4.7	01-2019	Ratified by the Ministry of the Interior and Kingdom Relations February 2019

1 Introduction to the Certificate Policy

1.1 Overview

This is part 3c of the Programme of Requirements (PoR) for the PKI for the government and is known as the Certificate Policy (CP). Set out in the PoR are the standards for the PKI for the government. This section relates to the requirements laid down for the services of a Trust Service Provider (TSP) within the PKI for the government. Within the PKI for the government, a distinction is made between various domains. This document only relates to the personal certificates issued by a TSP in the Citizen domain.

This chapter includes a brief explanation of the CP. A more detailed explanation regarding the background and structure of the PKI for the government, as well as the cohesion between the various parts within the PoR is included in part 1 of the PoR.

For a list of the definitions and abbreviations used in this section, please refer to part 4 of the PoR.

1.1.1 Design of the Certificate Policy

As stated in part 1 of the PoR, the requirements that form part of the CP consist of requirements ¹:

- that ensue from the Dutch legal framework in relation to the electronic signature;
- that ensue from the current version of the ETSI EN 319-411-2, QCP-n-qscd (ETSI CP OID 0.4.0.194112.1.2) for non-repudiation certificates;
- that ensue from the current version of the ETSI EN 319 411-1 standard where policy NCP+ is applicable to authenticity and confidentiality certificates;
- that are specifically drawn up by and for the PKIoverheid.

Incorporated in chapters 2 to 9 inclusive are references to the specific PKIoverheid requirements in the Additional Requirements. The table below shows the structure of the reference to the actual PKIoverheid requirement (PKIo requirement).

RFC 3647	Reference to the paragraph from the RFC 3647 structure to which the PKIo requirement relates. RFC 3647 is a PKIX framework of the Internet Engineering Task Force (IETF) and is the de facto standard for the structure of Certificate Policies and Certification Practice Statements ² .
Number	Unique number of the PKIo requirement. In each paragraph, consecutive numbering is used for the PKIo requirements. In combination with the RFC 3647 paragraph number, this forms a unique label for the PKIo requirement.

This CP also includes a number of provisions that are not formulated as PKIo requirements. These provisions do not make any demands on the TSPs within the PKI for the government, but do apply as a policy to the

¹For an explanation regarding the positioning of the requirements applicable within the PKI for the government, please refer to part 1 of the PoR.

²Chapters 2 to 9 inclusive only include those paragraphs from RFC 3647 to which a PKIo requirement applies.

PKI for the government. This concerns provisions from paragraphs 1.1, 1.1.1, 1.1.2, 1.2, 1.3, 1.4, 1.5, 8, 9.12.1, 9.12.2, 9.14 and 9.17.

The profiles used within PKIoverheid relating to the end user certificates are listed in appendix A. The certificate status information is listed in the basic requirements.

1.1.2 Status

This is version 4.7 of part 3c of the PoR. The current version has been updated up to 8 February 2019 inclusive.

The PA has devoted the utmost attention and care to the data and information incorporated in this CP. Nevertheless, it is possible that there are inaccuracies and imperfections. The PA accepts no liability for damage resulting from these inaccuracies or imperfections, nor is any liability assumed for damage caused by the use or distribution of this CP, if this CP is used for purposes other than for the use of certificates described in paragraph 1.4 of this CP.

1.2 References to this CP

Within the PKI for the government different structures or roots are used based on the SHA-256 algorithm (G2 and G3). Furthermore these structures are divided into different domains.

The G2 root is divided into an Organization, a Citizen and an Autonomous Devices domain.

Under the G3 root there are domains for Organization Person, Organization Services, Citizen, and Autonomous Devices.

Each CP is uniquely identified by an OID, in accordance with the following schedule.

OID	CP
2.16.528.1.1003.1.2.3.1	for the authenticity certificate, that contains the public key for identification and authentication. Under this OID OCSP certificates may be issued for use within the context of this CP part.
2.16.528.1.1003.1.2.3.2	for the signature certificate, that contains the public key for the qualified electronic signature
2.16.528.1.1003.1.2.3.3	for the confidentiality certificate that contains the public key for confidentiality

The OID is structured as follows: {joint-iso-itu-t (2). country (16). the Netherlands (528). Dutch organization (1). Dutch government (1003). PKI for the government (1). CP (2). citizen domain (3). authenticity (1)/non repudiation (2)/confidentiality (3). version number}.

If requirements only apply to one or two types of certificates, this is expressly specified by stating the Object Identifier (OID) referencing the applicable CP or CPs.

1.3 User Community

In the Government and Companies domain, the Organization domain and the Organization Person domain the distinction between subscriber and certificate holder is relevant because, in practice, the following situation is anticipated: the TSP has an agreement with the subscriber which stipulates that the TSP will issue certificates to the certificate holders to be appointed by the subscriber (for example, the subscriber's employees). In the Citizen domain, the subscriber and certificate holder are the same person. Where the subscriber is listed in the CP Citizen, this has to be interpreted as certificate holder. The citizen takes on the obligations of both the subscriber and the certificate holder.

Within the Citizen domain, the user community consists of certificate holders (the citizens that use the certificates) and relying parties who act with trust in certificates of the relevant certificate holders.

The parties within the user community are subscribers, certificate holders and relying parties.

- A subscriber is a natural person who enters into an agreement with a TSP for certification of the public keys. A subscriber is also a certificate holder.
- A certificate holder is an entity, characterized in a certificate as the holder of the private key that is linked to the public key provided in the certificate.
- A relying party is every natural or legal personality who is a recipient of a certificate and who acts with a reliance on that certificate.

1.4 Certificate Usage

The use of certificates issued under this CP relates to communication of certificate holders who act in a private capacity.

[OID 2.16.528.1.1003.1.2.3.1] Authenticity certificates, that are issued under this CP, can be used for reliable electronic identification and authentication of persons. This concerns both the mutual identification of people and identification between people and computerized devices.

Authenticity certificates that are issued under this CP cannot be used to identify people in cases where the law requires that the identity of persons may only be established using the document referred to in the Compulsory Identification Act (Wet op de identificatieplicht).

Under this OID OCSP responder certificates may be issued for use within the domain Citizen. Said certificates can be used to sign OCSP responses for use in the verification of the validity of the end user certificate. More information can be obtained in appendix A of the base requirements.

[OID 2.16.528.1.1003.1.2.3.2] Signature certificates, that are issued under this CP, can be used to verify electronic signatures, that have "the same legal consequences as a handwritten signature", as specified in article 15a, first and second paragraphs, in Title 1 of Book 3 of the Civil Code (Burgerlijk Wetboek) under section 1A and are qualified certificates as referred to in article 1.1, paragraph ss of the Telecommunications Act (Telecomwet).

[OID 2.16.528.1.1003.1.2.3.3] Confidentiality certificates, issued under this CP, can be used to protect the confidentiality of data that is

exchanged and/or stored in electronic form. This concerns both the mutual exchange between people and exchange between people and computerized devices.

1.5 Contact information Policy Authority

The PA is responsible for this CP. Questions relating to this CP can be put to the PA; the address can be found at: <http://www.logius.nl/pkioverheid>.

2 Publication and Repository Responsibilities

2.1 Electronic Repository

Contains no additional requirements.

2.2 Publication of TSP information

RFC 3647	2.2 Publication of TSP information
Number	2.2-pki03

RFC 3647	2.2 Publication of TSP information
Number	2.2-pki07

RFC 3647	2.2 Publication of TSP information
Number	2.2-pki156

3 Identification and Authentication

3.1 Naming

RFC 3647	3.1.3 Anonymity or pseudonymity of certificate holders
Number	3.1.3-pkio11

3.2 Initial Identity Validation

RFC 3647	3.2.3 Authentication of individual identity
Number	3.2.3-pkio21

RFC 3647	3.2.3 Authentication of individual identity
Number	3.2.3-pkio169

3.3 Identification and Authentication for Re-key Requests

Contains no additional requirements.

4 Certificate Life-Cycle Operational Requirements

4.1 Certificate Application

Contains no additional requirements.

4.4 Certificate Acceptance

Contains no additional requirements.

4.5 Key Pair and Certificate Usage

Contains no additional requirements.

4.9 Certificate Revocation and Suspension

RFC 3647	4.9.1 Circumstances for revocation
Number	4.9.1-pkio52

RFC 3647	4.9.3 Procedure for revocation request
Number	4.9.3-pkio57

RFC 3647	4.9.7 CRL issuance frequency
Number	4.9.7-pkio65

RFC 3647	4.9.9 On-line revocation/status checking availability
Number	4.9.9-pkio66

RFC 3647	4.9.9 On-line revocation/status checking availability
Number	4.9.9-pkio67

RFC 3647	4.9.9 On-line revocation/status checking availability
Number	4.9.9-pkio68

RFC 3647	4.9.9 On-line revocation/status checking availability
Number	4.9.9-pkio70

RFC 3647	4.9.9 On-line revocation/status checking availability
Number	4.9.9-pkio71

4.10 Certificate Status Service

Contains no additional requirements.

5 Facility, Management and Operational Controls

5.2 Procedural Controls

Contains no additional requirements.

5.3 Personnel Controls

Contains no additional requirements.

5.4 Audit Logging Procedures

RFC 3647	5.4.1 Types of events recorded
Number	5.4.1-pkio80

5.5 Records Archival

Contains no additional requirements.

5.7 Compromise and Disaster Recovery

RFC 3647	5.7.4 Business continuity capabilities after a disaster.
Number	5.7.4-pkio861

6 Technical Security Controls

6.1 Key Pair Generation and Installation

RFC 3647	6.1.1 Key pair generation for the TSP sub CA
Number	6.1.1-pkio87

RFC 3647	6.1.1 Key pair generation for the certificate holders
Number	6.1.1-pkio88

RFC 3647	6.1.1 Key pair generation for the certificate holders
Number	6.1.1-pkio89

RFC 3647	6.1.2 Private key and SSCD delivery to certificate holder
Number	6.1.2-pkio94

6.2 Private Key Protection and Cryptographic Module Engineering Controls

RFC 3647	6.2.3 Private key escrow of certificate holder key
Number	6.2.3-pkio99

RFC 3647	6.2.3 Private key escrow of certificate holder key
Number	6.2.3-pkio100

RFC 3647	6.2.3 Private key escrow of certificate holder key
Number	6.2.3-pkio101

RFC 3647	6.2.11 Cryptographic module rating
Number	6.2.11-pkio104

RFC 3647	6.2.11 Cryptographic module rating
Number	6.2.11-pkio105

RFC 3647	6.2.11 Cryptographic module rating
Number	6.2.11-pkio106

6.3 Other Aspects of Key Pair Management

RFC 3647	6.3.1 Public key archival
Number	6.3.1-pkio108

RFC 3647	6.3.2 Certificate operational periods and key pair usage periods
Number	6.3.2-pkio109

6.4 Activation data

RFC 3647	6.4.1 Activation data generation and installation
Number	6.4.1-pkio112

RFC 3647	6.4.1 Activation data generation and installation
Number	6.4.1-pkio113

6.5 Computer Security Controls

Contains no additional requirements.

6.6 Life Cycle Technical Controls

Contains no additional requirements.

6.7 Network Security Controls

Contains no additional requirements.

7 Certificate, CRL and OSCP profiles

7.1 Certificate Profile

RFC 3647	7.1 Certificate Profile
Number	7.1-pkio149

RFC 3647	7.1 Certificate Profile
Number	7.1-pkio177

7.2 CRL Profile

Contains no additional requirements.

7.3 OCSP Profile

RFC 3647	7.3 OCSP profile
Number	7.3-pkio123

8 Compliance Audit and Other Assessments

All subjects relating to the conformity assessment of the TSPs within the PKI for the government are covered in PoR part 2 And the basic requirements.

9 Other Business and Legal Matters

9.2 Financial Responsibility

RFC 3647	9.2.1 Insurance coverage
Number	9.2.1-pkio124

9.5 Intellectual Property Rights

Contains no additional requirements.

9.6 Representations and Warranties

RFC 3647	9.6.1 CA Representations and Warranties by TSPs
Number	9.6.1-pkio127

RFC 3647	9.6.1 CA Representations and Warranties by TSPs
Number	9.6.1-pkio129

RFC 3647	9.6.1 CA Representations and Warranties by TSPs
Number	9.6.1-pkio131

RFC 3647	9.6.1 CA Representations and Warranties by TSPs
Number	9.6.1-pkio132

9.8 Limitations of Liability

RFC 3647	9.8 Limitations of liability
Number	9.8-pkio133

9.12 Amendments

Contains no additional requirements.

9.13 Dispute Resolution Procedures

Contains no additional requirements.

9.14 Governing Law

Contains no additional requirements.

9.17 Other provisions

RFC 3647	9.17 Miscellaneous provisions
Number	9.17-pkio139

If by judicial decision one or more provisions of this CP are declared to be invalid or not applicable, this does not affect the validity and applicability of all other provisions.

Appendix A Certificate profiles

Profile of the certificate for the Citizen domain

Criteria

When defining the fields and attributes within a certificate, the following codes are used:

- V : Compulsory; indicates that the attribute is compulsory and **MUST** be used in the certificate.
- O : Optional; indicates that the attribute is optional and **MAY** be used in the certificate.
- A : Advised against; indicates that the attribute is advised against and **SHOULD NOT** be used in the certificate.

It is not allowed to use fields that are not specified in the certificate profiles.

For the extensions, fields/attributes are used that, in accordance with international standards, are critical, are marked in the 'Critical' column with 'yes' to show that the relevant attribute **MUST** be checked using a process by means of which a certificate is evaluated. Other fields/attributes are shown with 'no'.

Naming convention **Subject.commonName**

The following requirements apply to the CommonName of the Subject field. The main principle is that the TSP is responsible for correct entry of the CommonName. For a correct implementation this entails that the TSP has to be able to check each part that is entered. The CommonName has the following format³:

[aristocratic designation] [**Full first forename OR nickname**] [*initials other forenames OR full other forenames*] [surname prefixes + surname partner '-'] [aristocratic title] [**surname prefixes + surname at birth**]

whereby:

text in bold = compulsory part, style in accordance with Compulsory Identification Act document or presented Local Council Personal Records Database extract

Italic = compulsory part, choice from two options (full forenames or initials)

normal = optional part; if present, the style has to be the same as the Compulsory Identification Act document or the presented Local Council Personal Records Database extract

In principle, the TSP decides whether or not optional parts are allowed. If it prefers, the TSP can leave the choice for an option to the subscriber or the party requesting the certificate. If the CommonName becomes too long for the number of characters that are allowed, optional parts have to be omitted (starting with the replacement of other forenames by initials from the last to the first position) until the name fits in the maximum field length.

³ The presented order is not compulsory, the surname can also be given first followed by forenames/initials.

Citizen certificates

Basic attributes

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Version	V	MUST be set at 2 (X.509v3).	RFC5280	Integer	Describes the version of the certificate, the value 2 stands for X.509 version 3.
SerialNumber	V	A serial number that MUST uniquely identify the certificate within the publishing CA domain.	RFC5280	Integer	All end user certificates have to contain at least 8 bytes of unpredictable random data in the certificate's serial number (SerialNumber).
Signature	V	MUST be created on the algorithm, as stipulated by the PA.	RFC5280, ETSI TS 102176	OID	MUST be the same as the field signatureAlgorithm. For certificates under the G2 and G3 root certificate, only sha-256WithRSAEncryption is allowed.
Issuer	V	MUST contain a Distinguished Name (DN). The field has the following attributes:	PKIo, RFC3739, ETSI TS 102280		Attributes other than those mentioned below MUST NOT be used.
Issuer.countryName	V	See requirements 7.1-pkio174	ETSI TS101862, X520, ISO 3166	Printable String	
Issuer.OrganizationName	V	See requirements 7.1-pkio174	ETSI TS 102280	UTF8String	
Issuer. organizationalUnitName	O	See requirements 7.1-pkio174	ETSI TS 102280: 5.2.4	UTF8String	
Issuer.serialNumber	O	See requirements 7.1-pkio174	RFC 3739	Printable String	
Issuer.commonName	V	See requirements 7.1-pkio174	PKIo, RFC 3739	UTF8String	The commonName attribute MUST NOT be necessary in order to identify the issuing government body (no part of the Distinguished Name, requirement from RFC 3739)

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Issuer.organizationIdentifier	V/ N	The organizationalIdentifier field contains an identification of the issuing CA. This field MUST be present when the field subject.organizationIdentifier is present in the TSP certificate and MUST NOT be present when this field is not present in the TSP certificate.	EN 319 412-1	String	The syntax of the identification string is specified in paragraph 5.1.4 van ETSI EN 319 412-1 and contains: <ul style="list-style-type: none"> • 3 character legal person identity type reference; • 2 character ISO 3166 [2] country code; • hyphen-minus "-" (0x2D (ASCII), U+002D (UTF-8)); and • identifier (according to country and identity type reference).
Validity	V	MUST define the period of validity of the certificate according to RFC 5280.	RFC 5280	UTCTime	MUST include the start and end date for validity of the certificate in accordance with the applicable policy laid down in the CPS.
subject	V	The attributes that are used to describe the subject (end user) MUST mention the subject in a unique manner. The field has the following attributes:	PKIo, RFC3739, ETSI TS 102 280		MUST contain a Distinguished Name (DN). Attributes other than those mentioned below MUST NOT be used.
Subject.countryName	V	complete C with two-letter country code in accordance with ISO 3166-1. If an official alpha-2 code is missing, the TSP MAY use the user-assigned code XX.	RFC 3739, X520, ISO 3166, PKIo	PrintableString	The country code that is used in Subject.countryName MUST correspond with the subscriber's address in accordance with the accepted document or registry.
Subject.commonName	V	The commonName attribute MUST be entered in accordance with the Naming Convention Subject.commonName paragraph shown above.	RFC 3739, ETSI TS 102 280, PKIo	UTF8String	The contents of this field MUST correspond with the name given in the GBA. The Compulsory Identification Act document or other evidence (excerpt from the population register) can be used to demonstrate this. The use of commas as punctuation in the commonName is advised against due to possible technical conflicts when processing the certificate.
Subject.Surname	V/ O	A correct reproduction of the element of the name laid down in the CN. Based on the Compulsory Identification Act document.	RFC 3739	UTF8String	This field MUST show the subject's surname including surname prefixes correctly as shown on the Compulsory Identification Act document.

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Subject.givenName	V/ O	A correct reproduction of the element of the name laid down in the CN. Based on the Compulsory Identification Act document.	RFC 3739	UTF8String	This field MUST show the subject's first name(s) correctly as shown on the Compulsory Identification Act document.
Subject.stateOrProvinceName	A	The use is advised against. If present, this field MUST contain the province of the certificate holder's branch in accordance with an accepted document or Basic registry.	PKIo, RFC 3739	UTF8String	Name of the province MUST correspond with the certificate holder's address in accordance with the GBA. The certificate holder will have to submit recent proof of his address.
Subject.localityName	A	The use is advised against. If present, this field MUST contain the location of the certificate holder in accordance with an accepted document or Basic registry.	PKIo, RFC 3739	UTF8String	Name of the domicile MUST correspond with the certificate holder's address in accordance with the GBA. The certificate holder will have to submit recent proof of his address.
Subject.postalAddress	A	The use is advised against. If present, this field MUST contain the certificate holder's postal address in accordance with an accepted document or Basic registry.	PKIo, RFC 3739	UTF8String	The address MUST correspond with the certificate holder's address in accordance with the GBA. The certificate holder will have to submit recent proof of his address.
Subject.serialNumber	V	Number to be determined by the TSP. The combination of CommonName and Serialnumber MUST be unique within the context of the TSP.	RFC 3739, X 520, PKIo	Printable String	The serial number is intended to enable a distinction to be made between subjects with the same commonName. To avoid susceptibilities a serial Number attribute MUST be allocated to every subject.
subjectPublicKeyInfo	V	Contains, among other things, the public key.	ETSI TS 102 280, RFC 3279		Contains the public key, identifies the algorithm with which the key can be used.

Standard extensions

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
authorityKeyIdentifier	V	No	The algorithm to generate the AuthorityKey MUST be created on an algorithm determined by the PA.	ETSI TS 102 280, RFC 5280	BitString	The value MUST contain the SHA-1 hash from the authorityKey (public key of the TSP/CA).
SubjectKeyIdentifier	V	No	The algorithm to generate the subjectKey MUST be created on an algorithm determined by the PA.	RFC 5280	BitString	The value MUST contain the SHA-1 hash from the subjectKey (public key of the certificate holder).
KeyUsage	V	Yes	<p>The attribute extension specifies the intended purpose of the key incorporated in the certificate. In the PKI for the government, for each certificate type various bits are incorporated in the keyUsage extension.</p> <p>In authenticity certificates the digitalSignature bit MUST be incorporated and marked as being essential. Another keyUsage MUST NOT be combined with this.</p> <p>In confidentiality certificates, keyEncipherment and dataEncipherment bits MUST be incorporated and marked as being essential. Another keyUsage MUST NOT be combined with this.</p> <p>In certificates for the electronic signature the non-repudiation bit MUST be incorporated and marked as being essential. Another keyUsage MUST NOT be combined with this.</p>	RFC 3739, RFC 5280, ETSI TS 102 280	BitString	

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
CertificatePolicies	V	No	MUST contain the OID of the certificate policy (CP), the URI of the certification practice statement (CPS), and a user notice. The applicable PKI for the government OID scheme is described in the CP. The TSP SHOULD use UTF8String in the userNotice, but MAY use IA5String.	RFC 3739	OID, String, UTF8String or IA5String	For the Citizen domain, the OIDs are: 2.16.528.1.1003.1.2.3.1, 2.16.528.1.1003.1.2.3.2 and 2.16.528.1.1003.1.2.3.3. Reference to the paragraph numbers of the PoR/CP in the user notice is advised against because the persistency of this cannot be guaranteed (unlike the OID number of the CP).
SubjectAltName	V	No	MUST be used and given a personal worldwide unique identification number.	RFC 4043, RFC 5280, PKIo, ETSI 102 280		MUST include a unique identifier in the othername attribute. Attributes other than those mentioned below MUST NOT be used.
SubjectAltName.otherName	V		MUST be used containing a unique identification number that identifies the certificate holder. An additional othername entry MAY be included in the authentication certificate for use with SSO (Single Sign On).	PKIo	IA5String, Microsoft UPN, IBM Principal-Name, Kerberos PrincipalName or Permanent-Identifier	Includes an OID of the TSP awarded by the PA to the TSP and a number that is unique within the namespace of that OID that permanently identifies the subject, in one of the following ways: <ol style="list-style-type: none"> 1. MS UPN: [number]@[OID] 2. MS UPN: [OID].[number] 3. IA5String: [OID]-[number] 4. Permanent Identifier: Identifiervalue = [number] Assigner = [OID] Alternative 1. is also suitable for SSO. If a second othername for SSO is given in the certificate, the SSO othername MUST be given first in the SubjectAltName, before the PKIoverheid format othername described above, in order to ensure the proper operation of the SSO mechanism. It is recommended that an existing registration number from back office systems is used, in combination with a code for the organization. In combination with the TSP OID, this identifier is internationally unique. This number MUST be persistent.

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
SubjectAltName.rfc822Name	A		MAY be used for the certificate holder's e-mail address, for applications that need the e-mail address to be able to function properly.	RFC 5280	IA5String	<p>For PKIoverheid certificates, the use of e-mail addresses is advised against, because e-mail addresses of certificate holders often change and are susceptible to spam.</p> <p>If the e-mail address is included in the certificate, the TSP MUST:</p> <ul style="list-style-type: none"> • have the subscriber sign for approval, and; • check whether the email address belongs to the subscriber and that the subscriber has access to the email address (for example by performing a challenge response).
BasicConstraints	O	Yes	The "CA" field MUST be omitted (default value is then "FALSE").	RFC 5280		A (Dutch language) browser can then be seen: "Subjecttype = Eidentiteit", "Beperking voor padlengte = Geen" ("Subject type = End Entity", "Path length constraint = None")
CRLDistributionPoints	V	No	MUST include the URI of a CRL distribution point.	RFC 5280, ETSI TS 102 280		The reference MUST be accessible through the http or LDAP protocol. The attribute Reason MUST NOT be used, reference MUST be made to 1 CRL for all types of reasons for revocation. In addition to CRL, other types of certificate status information service MAY be supported.
ExtKeyUsage	V	No		RFC 5280		See requirement 7.1-pkio149
FreshestCRL	O	No	MUST contain the URI of a Delta CRL distribution point, if Delta CRLs are used.	RFC 5280, PKIo		Delta-CRLs are an optional extension. In order to fulfil the requirements of PKIoverheid a TSP MUST also publish full CRLs at the required release frequency.

Private extensions

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
authorityInfoAccess	O	No	This attribute MUST include the URI of an OCSRP responder if Online Certificate Status Protocol (OCSRP) plays a role.			This field can optionally be used to reference other additional information about the TSP.
SubjectInfoAccess	O	No		RFC 5280	OID, Generalname	This field can be used to reference additional information about the subject, provided that the information that is offered does not infringe the privacy of the subject.
BiometricInfo	O	No	Contains the hash of a biometric template and optionally a URI that references a file with the biometric template itself.	RFC 3739		
QcStatement	V/ N	No	<p>Certificates for the electronic signature MUST indicate that they are issued as qualified certificates complying with annex I of EU regulation 920/2014. This compliance is indicated by including the <i>id-etsi-qcs-QcCompliance</i> statement in this extension.</p> <p>Certificates for the electronic signature MUST indicate that they are issued as type of certificate complying with annex I of EU regulation 920/2014. This compliance is indicated by including the <i>id-etsi-qct-esign</i> statement in this extension.</p> <p>Certificates for the electronic signature MUST indicate that the private key that is part of the public key in the certificate is saved on a qualified signature creation device (QSCD) complying with annex II of EU regulation 920/2014. This compliance is</p>	RFC 3739, ETSI TS 102 280, ETSI TS 101 862	OID	<p>The aforementioned QcStatement identifiers relate to the following OIDs:</p> <ul style="list-style-type: none"> id-etsi-qcs-QcCompliance { id-etsi-qcs 1 } 0.4.0.1862.1.1 id-etsi-qct-esign { id-etsi-qcs-QcType 1 } 0.4.0.1862.1.6.1 id-etsi-qcs-QcSSCD { id-etsi-qcs 4 } 0.4.0.1862.1.4 id-etsi-qcs-QcPDS { id-etsi-qcs 5 } 0.4.0.1862.1.5

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
			<p>indicated by including the <i>id-etsi-qcs-QcSSCD</i> statement in this extension.</p> <p>Certificates for the electronic signature MUST contain a reference to the location of the PKI Disclosure Statement (PDS). This URL must present in the <i>id-etsi-qcs-QcPDS</i> statement in this extension.</p> <p>The certificates for authenticity and the certificates for confidentiality MUST NOT use this extension.</p>			

10 Revisions

10.1 Amendments from version 4.6 to 4.7

10.1.1 *New*

- Requirement 7.1-pkio177 (effective date immediately after publication PoR 4.7)
- Requirement 3.2.3-pkio169 (effective date 4 weeks after publication of PoR 4.7)

10.1.2 *Modifications*

- Description of a number of certificate attributes replaced by reference to requirement 7.1-pkio174 (effective date 8 weeks after publication PoR 4.7)
- Reference to CWA 14 169 amended to EN 419 211 for QSCDs. This also sets requirements for the issue of QSCDs for requirements 6.1.1-pkio88, 6.2.11-pkio104, 6.2.11-pkio105, 6.2.11-pkio106, 6.4.1-pkio112 and 4.9.1-pkio52 (effective date immediately after publication PoR 4.7)

10.2 Amendments from version 4.5 to 4.6

10.2.1 *Modifications*

- Modified reference to ETSI certificate profiles (effective date directly after publication of PoR 4.6)
- Certificate profile, removed exception subject.surName and subject.givenName (effective date directly after publication of PoR 4.6)
- Corrected subjectAltName.othername field (effective date directly after publication of PoR 4.6)

10.3 Amendments from version 4.4 to 4.5

10.3.1 *New*

- Mandatory English CPS (requirement 2.2-pkio3, effective date 1-10-2017)
- Mandatory yearly renewal CPS (requirement 2.2-pkio156, effective date 1-1-2017)

10.3.2 *Modifications*

- Requirement 4.9.9-pkio67 now references RFC6960 instead of RFC2560 (effective date 31-12-2016)
- Allow/require ECU emailProtection in authenticity and non-repudiation certificates in requirement 7.1-pkio149 (effective date 1-4-2017)
- Change in OID 2.16.528.1.1003.1.2.3.1 to also cover OCSP responder certificates (effective date 1-7-2017)
- Mandatory use of field "NextUpdate" in OCSP responses (requirement 4.9.9-pkio71, effective date 1-7-2017)

10.3.3 *Editorial*

- Removed typos from certificate profile.

10.4 Amendments from version 4.3 to 4.4

10.4.1 *New*

None

10.4.2 *Modifications*

- Removal of requirement 5.3.2-pkio79 (effective date 1-2-2017)
- Clarification of issuer.organizationIdentifier field (effective date 1-2-2017)
- Tightening of use optional EKUs that conflict with the parent TSP CA certificate (effective date 1-2-2017)
- Prohibition use of QCStatement with authenticity and confidentiality certificate (equalization of parts a, c &I, effective date 1-2-2017)

10.4.3 *Editorial*

- Replaced CSP (Certificate Service Provider) with TSP (Trust Service Provider) in accordance with eIDAS directive.

10.5 Amendments from version 4.2 to 4.3

10.5.1 *New*

- Addition of Issuer.organizationalIdentifier in the certificate profile (effective date 1-7-2016)

10.5.2 *Modifications*

- Description with attribute CertificatePolicies (effective date 1-7-2016)
- Removal of optional use KeyAgreement with Key Usage (effective date no later than 4 weeks after publication of PoR 4.3)
- Mandatory QcStatement in qualified certificate (effective date 1-7-2016)
- ETSI TS 102 176-1 replaced by ETSI TS 119 312 (effective date no later than 4 weeks after publication of PoR 4.3)
- Use of values in the BasicConstraints field no longer permitted in end entity certificates (effective date 1-7-2016)
- ETSI TS 102 042 replaced by ETSI EN 319 411-1 (effective date 1-7-2016 or when the accreditation to the certifying body has been granted with a final date of 30 June 2017)

10.5.3 *Editorial*

- Removed references to G1 Root (expired)

10.6 Amendments from version 4.1 to 4.2

10.6.1 *New*

- Requirement 7.1-pkio149 (effective date 1 juli 2016)

10.6.2 *Modifications*

None

10.6.3 *Editorial*

None

10.7 Amendments from version 4.0 to 4.1

10.7.1 *New*

- Certification against ETSI TS 102 042(effective date no later than 4 weeks after publication of PoR 4.1);

10.7.2 *Modifications*

- None

10.7.3 Editorial

- Small editorial modifications to the following requirements:
 - 3.1.3-pkio11;
 - 5.7.4-pkio86;
 - 9.6.1-pkio131.

10.8 Amendments from version 3.7 to 4.0

10.8.1 New

- None

10.8.2 Modifications

- PoR requirements have been renumbered according to a new naming convention;
- The creation of a document containing the baseline and additional requirements;
- Changes to requirements can be found in the baseline and additional requirements documents respectively.

10.8.3 Editorial

Editorial changes to requirements can be found in the baseline and additional requirements documents respectively. These changes have no effect on the content of the information.